

Spotboy Pro SR 50 2Way | 2X10W

Product Reference

Environment Indoor

Installation Semi Recess

Construction & Materials

Housing Die Cast Aluminium,Milled Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 2x9.0W

System Power Watts 2x10.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Spotboy Pro SR 50 2Way	2X10W	WW27K	CRI80	23°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Spotboy Pro SR 50 2Way	2X10W	2x948	92	2700K	WW27K	CRI80	23°(SS)	White SWH Non Dimmable On/Off
		2x979	95	3000K	WW30K	CRI90	30°(MD)	Black SBL Phase Dimmable PDIM
		2x1030	100	4000K	NW40K		33°(WD)	Custom CSM Dali Dimmable DDIM
		2x1051	102	5700K	CW57K		50°(VWD)	Bluetooth Dimmable BTTM
				2700K-5700K	TW			Casambi CBTM
				Warm to Dim	W2D			
Spotboy Pro SR 50 2Way	2X10W			WW27K	CRI80	23°(SS)	SWH	On/Off

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

www.abbylighting.com