

Birds on a Branch 1way | 1x8W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Die Cast Aluminium,Milled Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 7.4W

System Power Watts 8.5W

Operating Voltage Vin 220-240Vac

Power Factor p.f. >0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/180mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Birds on a Branch 1way	1x8W	WW27K	CRI80	24°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
Birds on a Branch 1way	1x8W	621	73	2700K	WW27K	CRI80	24°	24°	White	SWH	Non Dimmable	On/Off
		638	75	3000K	WW30K	CRI90	36°	36°	Black	SBL	Phase Dimmable	PDIM
		672	79	4000K	NW40K		52°	52°	Custom	CSM	Dali Dimmable	DDIM
		689	81	5700K	CW57K						Bluetooth Dimmable	BTTM
											Casambi	CBTM
Birds on a Branch 1way	1x8W			WW27K		CRI80	24°		SWH		On/Off	