

# T Zee Dropdown OPD 180 | 30W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Extruded and Sheet Aluminium

Primary Lens -

Primary Reflector White Optics

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 25.3W

System Power Watts 29.1W

Operating Voltage Vin 220-240Vac

Power Factor p.f. &gt;0.95



## Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/750mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>T Zee Dropdown OPD 180</b>	<b>30W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>101° general diffuse</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>T Zee Dropdown OPD 180</b>	<b>30W</b>	3055	105	2700K	<b>WW27K</b>	101° general diffuse	White	Non Dimmable
		3143	108	3000K	<b>WW30K</b>		Black	Phase Dimmable
		3288	113	4000K	<b>NW40K</b>		Custom	Dali Dimmable
		3346	115	5700K	<b>CW57K</b>			Casambi
				2700K-5700K	<b>TW</b>			
<b>T Zee Dropdown OPD 180</b>	<b>30W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>101° general diffuse</b>	<b>SWH</b>	<b>On/Off</b>