

# Mojo 65 48V VWD | 18W

## Product Reference

Environment Indoor

Installation Track Mounted

## Construction & Materials

Housing Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 17.8W

System Power Watts -

Operating Voltage Vin 48V

Power Factor p.f. >0.95



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/500mA

## Controls

Standard Switchable On/Off

Optional DDIM,BT,M,CASAMBI

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Mojo 65 48V VWD</b>	<b>18W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>51°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Mojo 65 48V VWD</b>	<b>18W</b>	2101	118	2700K	<b>WW27K</b>	51°	White	Non Dimmable <b>On/Off</b>
		2161	121	3000K	<b>WW30K</b>		Black	
		2262	127	4000K	<b>NW40K</b>		<b>SBL</b>	
		2303	129	5700K	<b>CW57K</b>			
				2700K-5700K	<b>TW</b>			
<b>Mojo 65 48V VWD</b>	<b>18W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>51°</b>	<b>SWH</b>	<b>On/Off</b>