

# Mojo 65 ITA MD | 28W

## Product Reference

Environment Indoor

Installation Track Mounted

## Construction & Materials

Housing Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 24.6W

System Power Watts 28.3W

Operating Voltage Vin 220-240Vac

Power Factor p.f. >0.95

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Mojo 65 ITA MD</b>	<b>28W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>27°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
<b>Mojo 65 ITA MD</b>	<b>28W</b>	2434	86	2700K	<b>WW27K</b>	<b>CRI80</b>	27°	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		2519	89	3000K	<b>WW30K</b>	CRI90		Black	<b>SBL</b>		
		2660	94	4000K	<b>NW40K</b>						
		2717	96	5700K	<b>CW57K</b>						
<b>Mojo 65 ITA MD</b>	<b>28W</b>			<b>WW27K</b>		<b>CRI80</b>	<b>27°</b>	<b>SWH</b>		<b>On/Off</b>	



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/700mA

## Controls

Standard Switchable On/Off

Optional -