

Nexus 150 Soft P MPD 240 | 56W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 47.3W

System Power Watts 54.4W

Operating Voltage Vin 220V- 240V/50-60Hz

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/1400mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nexus 150 Soft P MPD 240	56W	WW27K	CRI80	104°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Nexus 150 Soft P MPD 240	56W	4950	91	2700K	WW27K	104° -	White	Non Dimmable
		5114	94	3000K	WW30K		Black	Dali Dimmable
		5386	99	4000K	NW40K		Custom	Casambi
		5494	101	5700K	CW57K			
				2700K-5700K	TW			
Nexus 150 Soft P MPD 240	56W			WW27K	CRI80	104°	SWH	On/Off