

# Black Jack FR | 8W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 7.1W

System Power Watts 8.2W

Operating Voltage Vin 220V- 240V/50-60Hz

Power Factor p.f. &gt;0.95



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/200mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Black Jack FR</b>	<b>8W</b>	<b>WW27K</b>	<b>CRI90</b>	<b>30°(MD)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
<b>Black Jack FR</b>	<b>8W</b>	476	58	2700K	<b>WW27K</b>	<b>CRI90</b>	30°(MD)	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		492	60	3000K	<b>WW30K</b>		44°(WD)	Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		517	63	4000K	<b>NW40K</b>	Custom	<b>CSM</b>	Dali Dimmable	<b>DDIM</b>		
		533	65	5700K	<b>CW57K</b>					Casambi	<b>CBTM</b>
<b>Black Jack FR</b>	<b>8W</b>			<b>WW27K</b>	<b>CRI90</b>	<b>30°(MD)</b>	<b>SWH</b>			<b>On/Off</b>	