

# Roa R OPD 240 | 40W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 35.0W

System Power Watts 40.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



## Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/1050mA

### Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Roa R OPD 240</b>	<b>40W</b>	<b>WW27K</b>	<b>CR180</b>	<b>100°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Roa R OPD 240</b>	<b>40W</b>	4261	106	2700K	<b>WW27K</b>	100°	White	Non Dimmable Dali Dimmable Casambi
		4382	109	3000K	<b>WW30K</b>		Black	
		4583	114	4000K	<b>NW40K</b>		Custom	
		4703	117	5700K	<b>CW57K</b>			
				2700K-5700K	<b>TW</b>			
<b>Roa R OPD 240</b>	<b>40W</b>			<b>WW27K</b>	<b>CR180</b>	<b>100°</b>	<b>SWH</b>	<b>On/Off</b>