

# Roa S OPD 60 | 20W

## Product Reference

Environment Indoor

Installation Ceiling Surface

## Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 16.7W

System Power Watts 19.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



## Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/500mA

### Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Roa S OPD 60</b>	<b>20W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>100°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Roa S OPD 60</b>	<b>20W</b>	1939	101	2700K	<b>WW27K</b>	<b>CRI80</b>	100°	White <b>SWH</b> Non Dimmable <b>On/Off</b>
		1997	104	3000K	<b>WW30K</b>		CRI90	Black <b>SBL</b> Dali Dimmable <b>DDIM</b>
		2093	109	4000K	<b>NW40K</b>		Custom <b>CSM</b> Casambi <b>CBTM</b>	
		2131	111	5700K	<b>CW57K</b>			
				2700K-5700K	<b>TW</b>			
<b>Roa S OPD 60</b>	<b>20W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>100°</b>	<b>SWH</b>	<b>On/Off</b>