

# Outline Wallgrazer 120 |

## 40W

### Product Reference

Environment Outdoor

Installation Ceiling Surface

### Construction & Materials

Housing Extruded Aluminium

Primary Lens Polycarbonate

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 34.1W

System Power Watts 39.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt;0.95



### Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/1000mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                          | Watt       | CCT          | CRI          | Angle           | Finish    | Control       |
|---------------|-------------------------------|------------|--------------|--------------|-----------------|-----------|---------------|
|               | <b>Outline Wallgrazer 120</b> | <b>40W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>91°x 30°</b> | <b>AL</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                          | WATT       | LUMEN | EFFICACY | CCT          | CRI          | ANGLE           | FINISH             | CONTROL       |              |                    |             |
|-------------------------------|------------|-------|----------|--------------|--------------|-----------------|--------------------|---------------|--------------|--------------------|-------------|
| <b>Outline Wallgrazer 120</b> | <b>40W</b> | 4077  | 104      | 2700K        | <b>WW27K</b> | 91°x 30°        | Anodised Aluminium | <b>AL</b>     | Non Dimmable | <b>On/Off</b>      |             |
|                               |            | 4194  | 107      | 3000K        | <b>WW30K</b> |                 |                    |               | CRI90        | Phase Dimmable     | <b>PDIM</b> |
|                               |            | 4390  | 112      | 4000K        | <b>NW40K</b> |                 |                    |               |              | Dali Dimmable      | <b>DDIM</b> |
|                               |            | 4469  | 114      | 5700K        | <b>CW57K</b> |                 |                    |               |              | Bluetooth Dimmable | <b>BTTM</b> |
|                               |            |       |          | 2700K-5700K  | <b>TW</b>    |                 |                    |               |              | Casambi            | <b>CBTM</b> |
| <b>Outline Wallgrazer 120</b> | <b>40W</b> |       |          | <b>WW27K</b> | <b>CRI80</b> | <b>91°x 30°</b> | <b>AL</b>          | <b>On/Off</b> |              |                    |             |