

ZuG Dark P 224 | 50W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Aluminium Extrusion

Primary Lens PMMA

Primary Reflector -

Secondary Reflector PC Black Cover

Body Finish White,Black

Diffuser -

Antiglare Baffle Black,White,Custom

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 43.1W

System Power Watts 49.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Osram/Cree 3030 LED array 39V-42Vdc/1050mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	ZuG Dark P 224	50W	WW27K	CRI80	28°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI		ANGLE		FINISH		CONTROL	
ZuG Dark P 224	50W	5495	111	2700K	WW27K	CRI80	28°(MD)	28°(MD)	White	SWH	Non Dimmable	On/Off	
		5643	114	3000K	WW30K	CRI90	66°(VWD)		Black	SBL	Phase Dimmable	PDIM	
		5940	120	4000K	NW40K							Dali Dimmable	DDIM
		6039	122	5700K	CW57K							Bluetooth Dimmable	BTTM
											Casambi	CBTM	
ZuG Dark P 224	50W			WW27K	CRI80		28°(MD)		SWH			On/Off	