

# Dark Knight A 15 | 35W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster – ABS

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed,Adjustable

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 28.9

System Power Watts 33.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI90

Led Type SMD high power

LED Fitted -

### Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Dark Knight A 15</b>	<b>35W</b>	<b>WW27K</b>	<b>CRI90</b>	<b>20°(SS)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
<b>Dark Knight A 15</b>	<b>35W</b>	2224	67	2700K	<b>WW27K</b>	20°(SS) 30°(MD)	White	<b>SWH</b>	Non Dimmable <b>On/Off</b>
		2324	70	3000K	<b>WW30K</b>		30°(MD)	Black	<b>SBL</b>
		2523	76	4000K	<b>NW40K</b>	49°(WD)	Custom	<b>CSM</b>	Casambi <b>CBTM</b>
		2590	78	5700K	<b>CW57K</b>				
					2700K-5700K	<b>TW</b>			
<b>Dark Knight A 15</b>	<b>35W</b>			<b>WW27K</b>	<b>CRI90</b>	<b>20°(SS)</b>	<b>SWH</b>	<b>On/Off</b>	