

Dark Knight R Wash | 17W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster – ABS

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 14.6W

System Power Watts 16.8W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Dark Knight R Wash	17W	WW27K	CRI90		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Dark Knight R Wash	17W	941	56	2700K	WW27K		White	SWH	Non Dimmable	On/Off
		974	58	3000K	WW30K		Black	SBL	Phase Dimmable	PDIM
		1042	62	4000K	NW40K		Custom	CSM	Dali Dimmable	DDIM
		1075	64	5700K	CW57K				Bluetooth Dimmable	BTTM
								Casambi	CBTM	
Dark Knight R Wash	17W			WW27K	CRI90		SWH	On/Off		