

Rio V2 | 15W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector Anodised

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 12.5W

System Power Watts 14.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Rio V2	15W	WW27K	CRI80	22°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL		
Rio V2	15W	965	67	2700K	WW27K	CRI80	22°(SS)	24°(MD)	White	SWH	Non Dimmable	On/Off	
		1008	70	3000K	WW30K	CRI90	24°(MD)		Black	SBL	Phase Dimmable	PDIM	
		1066	74	4000K	NW40K		33°(WD)		Custom	CSM	Dali Dimmable	DDIM	
		1094	76	5700K	CW57K							Bluetooth Dimmable	BTTM
						2700K-5700K	TW					Casambi	CBTM
				Warm to Dim	W2D								
Rio V2	15W				WW27K	CRI80		22°(SS)		SWH		On/Off	