

iKapp Wash 50 | 10W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 9.2W

System Power Watts 10.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	iKapp Wash 50	10W	WW27K	CRI80		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL			
iKapp Wash 50	10W	880	83	2700K	WW27K	CRI80	White	SWH	Non Dimmable	On/Off	
		965	91	3000K	WW30K		CRI90		Black	Phase Dimmable	PDIM
		1028	97	4000K	NW40K		Custom		CSM	Dali Dimmable	DDIM
		1060	100	5700K	CW57K				Bluetooth Dimmable	BTTM	
				2700K-5700K	TW				Casambi	CBTM	
				Warm to Dim	W2D						
iKapp Wash 50	10W			WW27K	CRI80		SWH	On/Off			