

# Spotboy SR 50 2Way | 2X15W

## Product Reference

Environment Indoor

Installation Semi Recess

## Construction & Materials

Housing Die Cast Aluminium,Milled Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 2x12.6W

System Power Watts 2x14.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



## Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Spotboy SR 50 2Way</b>	<b>2X15W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>20°(ss)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Spotboy SR 50 2Way</b>	<b>2X15W</b>	2x1349	93	2700K	<b>WW27K</b>	<b>CRI80</b>	20°(SS)	White <b>SWH</b> Non Dimmable <b>On/Off</b>
		2x1392	96	3000K	<b>WW30K</b>	CRI90	26°(MD)	Black <b>SBL</b> Phase Dimmable <b>PDIM</b>
		2x1494	103	4000K	<b>NW40K</b>		33°(WD)	Custom <b>CSM</b> Dali Dimmable <b>DDIM</b>
		2x1537	106	5700K	<b>CW57K</b>			Bluetooth Dimmable <b>BTTM</b>
				2700K-5700K	<b>TW</b>			Casambi <b>CBTM</b>
				Warm to Dim	<b>W2D</b>			
<b>Spotboy SR 50 2Way</b>	<b>2X15W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>20°(ss)</b>	<b>SWH</b>	<b>on/off</b>

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

[www.abbylighting.com](http://www.abbylighting.com)