

# Tiny Wash | 10W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Aluminium

Primary Lens Polycarbonate

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 8.3W

System Power Watts 10.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/250mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

| Code Example: | Name             | Watt       | CCT          | CRI          | Angle | Finish     | Control       |
|---------------|------------------|------------|--------------|--------------|-------|------------|---------------|
|               | <b>Tiny Wash</b> | <b>10W</b> | <b>WW27K</b> | <b>CRI80</b> |       | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME             | WATT       | LUMEN | EFFICACY | CCT          | CRI          | ANGLE        | FINISH     | CONTROL       |                    |               |             |
|------------------|------------|-------|----------|--------------|--------------|--------------|------------|---------------|--------------------|---------------|-------------|
| <b>Tiny Wash</b> | <b>10W</b> | 426   | 41       | 2700K        | <b>WW27K</b> | <b>CRI80</b> | White      | <b>SWH</b>    | Non Dimmable       | <b>On/Off</b> |             |
|                  |            | 468   | 45       | 3000K        | <b>WW30K</b> | CRI90        | Black      | <b>SBL</b>    | Phase Dimmable     | <b>PDIM</b>   |             |
|                  |            | 499   | 48       | 4000K        | <b>NW40K</b> |              | Custom     | <b>CSM</b>    | Dali Dimmable      | <b>DDIM</b>   |             |
|                  |            | 520   | 50       | 5700K        | <b>CW57K</b> |              |            |               | Bluetooth Dimmable | <b>BTTM</b>   |             |
|                  |            |       |          |              | 2700K-5700K  | <b>TW</b>    |            |               |                    | Casambi       | <b>CBTM</b> |
|                  |            |       |          |              | Warm to Dim  | <b>W2D</b>   |            |               |                    |               |             |
| <b>Tiny Wash</b> | <b>10W</b> |       |          | <b>WW27K</b> | <b>CRI80</b> |              | <b>SWH</b> | <b>On/Off</b> |                    |               |             |