

Nova 14 | 36W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing CRCA

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material -

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 30.0W

System Power Watts 34.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 26V-32Vdc/1000mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nova 14	36W	WW27K	CRI80	95°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Nova 14	36W	3209	93	2700K	WW27K	CRI80	95°	White	SWH	Non Dimmable	On/Off
		3312	96	3000K	WW30K	CRI90				Phase Dimmable	PDIM
		3519	102	4000K	NW40K					Dali Dimmable	DDIM
		3623	105	5700K	CW57K					Bluetooth Dimmable	BTTM
										Casambi	CBTM
Nova 14	36W			WW27K	CRI80	95°	SWH			On/Off	