

# Jugnu | 8W

## Product Reference

Environment Outdoor

Installation Ceiling Surface, Floor Surface, Wall Surface, Wall Surface

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens Tempered Glass Visor

Primary Reflector PC metallised

Secondary Reflector -

Body Finish Black, Grey

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 6.6W

System Power Watts 8.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Jugnu</b>	<b>8W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>13°(SS)</b>	<b>SBL</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
<b>Jugnu</b>	<b>8W</b>	531	64	2700K	<b>WW27K</b>	<b>CRI80</b>	13°(SS)	Black	<b>SBL</b>	Non Dimmable	<b>On/Off</b>
		564	68	3000K	<b>WW30K</b>	CRI90	28°(MD)	Grey	<b>GGT</b>		
		598	72	4000K	<b>NW40K</b>		60°(WD)				
		614	74	5700K	<b>CW57K</b>						
<b>Jugnu</b>	<b>8W</b>			<b>WW27K</b>		<b>CRI80</b>	<b>13°(SS)</b>	<b>SBL</b>			<b>On/Off</b>



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80, CRI90

Led Type COB

LED Fitted CREE COB LED 9Vdc/700mA

## Controls

Standard Switchable On/Off

Optional Non Dimmable