

Go Pro 50 ITA | 20W

Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 17.4W

System Power Watts 20.0W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/500mA

Controls

Standard Switchable On/Off

Optional Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|----------------------|------------|--------------|--------------|----------------|------------|---------------|
| | Go Pro 50 ITA | 20W | WW27K | CRI80 | 24°(SS) | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | | CRI | ANGLE | FINISH | | CONTROL | |
|----------------------|------------|-------|----------|--------------|--------------|--------------|----------------|------------|------------|---------------|---------------|
| Go Pro 50 ITA | 20W | 1880 | 94 | 2700K | WW27K | CRI80 | 24°(SS) | White | SWH | Non Dimmable | On/Off |
| | | 1940 | 97 | 3000K | WW30K | CRI90 | 32°(MD) | Black | SBL | | |
| | | 2040 | 102 | 4000K | NW40K | | 36°(WD) | | | | |
| | | 2080 | 104 | 5700K | CW57K | | 46°(VWD) | | | | |
| Go Pro 50 ITA | 20W | | | WW27K | | CRI80 | 24°(SS) | SWH | | On/Off | |