

# Go Pro 35 HGB | 15W

## Product Reference

Environment Indoor

Installation Track Mounted

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 12.3W

System Power Watts 14.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Go Pro 35 HGB</b>	<b>15W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>29°(MD)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL		
<b>Go Pro 35 HGB</b>	<b>15W</b>	1424	101	2700K	<b>WW27K</b>	<b>CRI80</b>	29°(MD)	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>	
		1466	104	3000K	<b>WW30K</b>	CRI90	37°(WD)	Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>	
		1537	109	4000K	<b>NW40K</b>		56°(VWD)				Dali Dimmable	<b>DDIM</b>
		1565	111	5700K	<b>CW57K</b>						Bluetooth Dimmable	<b>BTTM</b>
				2700K-5700K	<b>TW</b>						Casambi	<b>CBTM</b>
				Warm to Dim	<b>W2D</b>							
<b>Go Pro 35 HGB</b>	<b>15W</b>			<b>WW27K</b>		<b>CRI80</b>	<b>29°(MD)</b>	<b>SWH</b>		<b>On/Off</b>		