

Tango Pro 75 | 28W

Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 23.7W

System Power Watts 27.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/700mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Tango Pro 75	28W	WW27K	CRI80	22°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Tango Pro 75	28W	2475	91	2700K	WW27K	CRI80	22°(SS)	White	SWH	Non Dimmable	On/Off
		2557	94	3000K	WW30K	CRI90	37°(MD)	Black	SBL	Phase Dimmable	PDIM
		2693	99	4000K	NW40K		54°(WD)			Dali Dimmable	DDIM
		2747	101	5700K	CW57K					Casambi	CBTM
						2700K-5700K	TW				
				Warm to Dim	W2D						
Tango Pro 75	28W				WW27K	CRI80	22°(SS)		SWH		On/Off