

# Spot On Framer ITA 55 | 18W

## Product Reference

Environment Indoor

Installation Track Mounted

## Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 15.7W

System Power Watts 18.0W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/450mA

## Controls

Standard Switchable On/Off

Optional Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Spot On Framer ITA 55</b>	<b>18W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>22°-29°</b>	<b>SBL</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
<b>Spot On Framer ITA 55</b>	<b>18W</b>	468	26	2700K	<b>WW27K</b>	<b>CRI80</b>	22°-29°	Black	<b>SBL</b>	Non Dimmable	<b>On/Off</b>
		486	27	3000K	<b>WW30K</b>	CRI90					
		522	29	4000K	<b>NW40K</b>						
		540	30	5700K	<b>CW57K</b>						
<b>Spot On Framer ITA 55</b>	<b>18W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>22°-29°</b>	<b>SBL</b>		<b>On/Off</b>		