

Lensed Wallwasher | 10W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 8.0W

System Power Watts 10W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Lensed Wallwasher	10W	WW27K	CRI80		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Lensed Wallwasher	10W	490	49	2700K	WW27K	CRI80		White	SWH	Non Dimmable	On/Off
		510	51	3000K	WW30K	CRI90		Black	SBL	Phase Dimmable	PDIM
		540	54	4000K	NW40K					Dali Dimmable	DDIM
		550	55	5700K	CW57K					Bluetooth Dimmable	BTTM
					Warm to Dim	W2D					Casambi
Lensed Wallwasher	10W			WW27K		CRI80		SWH		On/Off	